

# THE DOUBLE VERY DESCRIPTION OF THE PROPERTY OF

and are the minimum threse presents single come:

UNITED STATES DEPARTMENT OF COMMERCE
United States Patent and Trademark Office

November 12, 2004

THIS IS TO CERTIFY THAT ANNEXED HERETO IS A TRUE COPY FROM THE RECORDS OF THE UNITED STATES PATENT AND TRADEMARK OFFICE OF THOSE PAPERS OF THE BELOW IDENTIFIED PATENT APPLICATION THAT MET THE REQUIREMENTS TO BE GRANTED A FILING DATE.

APPLICATION NUMBER: 60/509,820 FILING DATE: October 08, 2003

RELATED PCT APPLICATION NUMBER: PCT/US04/33540

Certified by

Jon W Dudas

Acting Under Secretary of Commerce for Intellectual Property and Acting Director of the U.S. Patent and Trademark Office



BEST AVAILABLE COPY

Express in	ii Laber ito.							)
		ī	NVENTOR(S	5)				00746
61 - No. 42 - 1			<u></u>	-		Resid	ence	7.46
Given Name (first and	Family Name or Surname			(City and either State or Foreign Country			<del>-</del> 2	
Brian E. Joshua D.		Boehmer			Bartlett, Tenne			٦
John P.		Crews			Memphis, Tennessee			
Joill F.		Erspamer	_		Lakeland, Tennessee			
Additional in	ventors are being		<del></del>		y numbered sheets	attached	herelo	
		ITLE OF THE INV		00 cha	racters max)		_	
LATENT CARBO	N DIOXIDE G	ENERATING M	IATERIAL					
•								
Direct all corresponden	ce to: COI	RRESPONDENCE	E ADDRESS	i			- ** <del>-</del>	
X Customer Number	er:	07278		7				
OR	<u> </u>			_				
Firm or	Sandra S. Le	26	<del></del>					
Individual Name	DARBY & DA							
Address	P.O. Box 52		•					
City	New York		State	NY		Zip	10150-5257	
Country	US		Telephone	(21	2) 527-7700	Fax	(212) 753-6237	
	ENC	LOSED APPLICA	TION PART	S (ch	eck all that apply)			
x Specification N	umber of Page	s 12	CE	)(s), 1	Number			
	-	<del></del>	=			<u> </u>		$\neg$
x Drawing(s) Num	nder or Sneets	1		her	1			
x Application Dat	a Sheet. See	37 CFR 1.76	(sp	ecify	): [			
METHOD OF PAYME	NT OF FILING	FEES FOR THIS	PROVISION	AL A	PPLICATION FOR	PATEN	<u>π</u>	
		tatus. See 37 C						
							FILING FEE	
X A check or mor	ney order is end	closed to cover the	ne filing fees	i.			AMOUNT (\$)	
X The Director is	hereby authori	zed to charge fili	ng					
fees or credit any overpayment to Deposit Account Number: 04-0100 160.00								
Payment by cre	edit card. Form	PTO-2038 is at	tached.					
The invention was ma	ade by an agenc	y of the United Sta	tes Governme	ent or	under a contract witi	h an age	ency of the	
United States Govern		•						
		e U.S. Governmen						
L L and	the Governmen	nt contract number		,				_
Respectfully submitted	1.		[Page 1 of 1	1	Data			
ricopoularly coommittee	•	_			Date	Oct	ober 8, 2003	
SIGNATURE	Sandy	- lee						
TYPED OR	0				REGISTRATION I	NO.	51,932	
PRINTED NAME	Sandra S.	Lee		. (	(if appropriate)	_	51,932	
TELEPHONE	(212) 527-	7735		í	Docket Number:	01	313/0200131-US	<b>S</b> 0
	USE ONLY	OD EII INC A DE	ONECONAL	ADD	U ICATION EOD E	ATEN	-	
	USE UNLT P	OR FILING A PR	COVISIONAL	. APP	PLICATION FOR P	AIEN	•	

Dated:

Express Mail Label No.

PIL	<i>//</i> 36/17 (10-02)
Approved for use through,10/31/2002, Q	MB 0651-0032
nder the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB (	control number.

FEE TRANSFULL ALL FOR FY 2003  Patent fees a real subject to stream freshold.  Pagilization Number Not Yet Assigned Filing Date Filing Dat	CCC TO AMOMETAL			Compl t if Known						
Patent neas are subject to annual rentsy status. See 37 CFR 1.27  TOTAL AMOUNT OF PAYMENT (\$) 160.00  METHOD OF PAYMENT (check of that apply)  X check Oreal Moder Oreal Moder Oreal Notes (check of that apply)  X check Oreal Moder Oreal Notes (check of that apply)  X check Oreal Moder Oreal Notes (check of that apply)  X check Oreal Moder Oreal Notes (check of that apply)  X check Oreal Moder Oreal Notes (check of that apply)  X check Oreal Moder Oreal Notes (check of that apply)  X check Oreal Moder Oreal Notes (check of that apply)  X check Oreal Moder Oreal Notes (check of that apply)  X check Oreal Moder Oreal Notes (check of that apply)  X check Oreal Moder Oreal Notes (check of that apply)  X check Oreal Moder Oreal Notes (check of that apply)  X check Oreal Moder Oreal Notes (check of that apply)  X check Oreal Notes (check	FEE TRANSMITTAL		Application Number Not Yet Assigned							
Patent fees are subject to annual revision.    Applicant claims small entity status. See 37 CFR 127   Group Art Unit   N/A	for EV 2002		Filing Date			Concurrently				
Applicant claims small entity status. See 37 CFR 1.27   TOTAL AMOUNT OF PAYMENT (\$) 160.00   Attomey Docket No. 01313/0200131-US0						tor E	Brian E. Boehmer			
TOTAL AMOUNT OF PAYMENT (\$) 160.00 Attorney Docket No. 01313/0200131-USO  METHOD OF PAYMENT (check all that apply)  X check Cond Motey Other No. 01313/0200131-USO  METHOD OF PAYMENT (check all that apply)  X check Cond Motey Other No. 01313/0200131-USO  Deposit Account  Deposit Account  Large Eritly Small Entity Fee Fee Fee Code (\$) Fee Description  Charge fively indicated betwow X covery from the filing fee 100.00 Standard deposit account.  1051 130 2051 65 Surcharge - late provisional filing fee or cover shorted to the above-identified deposit account.  1052 1053 130 Non-English specification  1053 130 Non-English specification  1054 120 205 25 Surcharge - late provisional filing fee or cover shorted to the above-identified deposit account.  1055 1,840* 1805 1,840* Requisiting publication of SIR offer to be above-identified deposit account.  1056 1,840* 1805 1,840* Requisiting publication of SIR offer to be above-identified deposit account.  1057 1,840* Requisiting publication of SIR offer to be above-identified deposit account.  1058 1,840* 1805 1,840* Requisiting publication of SIR offer to be above-identified deposit account.  1058 1,840* 1805 1,840* Requisiting publication of SIR offer to be above-identified deposit account.  1058 1,840* 1805 1,840* Requisiting publication of SIR offer to be above-identified deposit account.  1059 1,840* 1805 1,840* Requisiting publication of SIR offer to be above-identified deposit account.  1050 1,840* 1805 1,840* Requisiting publication of SIR offer to be above-identified deposit account.  1050 1,840* 1805 1,840* Requisiting publication of SIR offer to be above-identified deposit account.  1051 130 2003 200 200 130* Using filing fee 1050.00  1052 160 2005 80 Provisional filing fee 1050.00  1053 150 2005 200 500 Provisional filing fee 1050.00  1054 150 2004 370 Reissue filing fee 1050.00  1055 160 2005 80 Provisional filing fee 1050.00  1055 160 2005 80 Provisional filing fee 1050.00  1055 160 2005 80 Provisional filing fee 1050.00  1056 160 2005 80 Provisional filing f	Patent rees are subject to annual revision.					ssigned				
METHOD OF PAYMENT (check all that apply)    X Check	Applicant claims small entity status. See 37 CFR 1.27	Group Art Unit			١	N/A				
X Check   Cord   Order   Other   None   Other   None   Other	TOTAL AMOUNT OF PAYMENT (\$) 160.00	コ	Attom	ey Doo	ket No	. (	01313/02	00131-US0		
X Check   Cord   Order   Other   None   Other   None   Other	METHOD OF PAYMENT (check all that apply)	一			FEE	CALCUL	ATION (co	ntinued)		
Deposit Account	Credit Money	2.4	DOITI	SMAI		0				
Large Entity   Small Entity   Smal		3. ADDITIONAL FEES								
Account   Annual   Account   Account   Annual   Account   Annual   Account   Account   Account   Annual   Account   A		Large	Entity	Small	Entity					
Decorat	Account						Fee Desc	ription	Foo Baid	
Account   Name   The Commissioner is hereby authorized to: (check at that apply)   1052 50   2052 25   Surcharge – late provisional filing fee or cover sheet.   1053 130   10					•	0	lata fila a fa			
Description   Charge feetes   Indicated below   X Credit any oversyments   1053   130   1053   130   1053   130   Non-English specification     Charge feetes   Indicated below   X Credit any oversyments   1612   2,520   1812   2,520   2,5	Account	1051	130	2051	65	_	-			
Charge any additional fee(s) during the pendency of this application   Charge fee(s) indicated below, except for the filling fee   1804 920*   1804 920*   Requesting publication of SIR prior to Examiner action   Requesting publication of SIR prior to Examine action   Requesting publication of SIR prior to Examiner action   Requesting publication of SIR prior to Examiner action   Requesting publication of SIR prior to Examiner action   Requestin		1052	50	2052	25		iate provisio	nai ning tee of cover		
Charge feete s indicated below, except for the filling fee   1804   920   1804	Charge fee(s) indicated below X Credit any overpayments	1053	130	1053	130	Non-English	specification	1		
Substitute   Sub		1812	2,520	1812		-	•		$\vdash$	
Design Fee   Pee   Calculation   1805   1,840*   1805   1	I = " " "					Requesting	publication o		<del>  </del>	
FEE CALCULATION   1251   150   1505						-		f SIR after		
1. BASIC FILING FEE   Large Entity   Small Entity   Fee		4	. 1		1,040	Examiner ad	ction			
Large Entity   Small Entity   Fee		4 -					• •		$\vdash$	
Total Claims		1							$\vdash \vdash \vdash$	
1001   740   2001   370   Utility filing fee   1401   320   2255   380   Extension for reply within fifth month   1002   330   2002   165   Design filing fee   1401   320   2401   160   Notice of Appeal   1004   740   2004   370   Reissue filing fee   1402   320   2403   140   Request for oral hearing   1005   160   2005   80   Provisional filing fee   160.00   1451   1,510   Petition to Institute a public use proceeding   1452   110   2452   55   Petition to revive - unavoidable   1453   1,280   2453   640   Petition to revive - unavoidable   1453   1,280   2453   640   Petition to revive - unavoidable   1501   1,280   2501   640   Utility issue fee (or reissue)   1502   460   2502   230   Design issue fee   160,000   160   130   1450   1450   130   1450   130   1450   130   1450   130   1450   130   1450   130   1450   130   1450   130   1450   130   1450   130   1450	Fee Fee Fee Fee Fee Description									
1002   330   2002   165   Design filing fee   1401   320   2401   160   Notice of Appeal   1402   320   2402   160   Filing a brief in support of an appeal   1403   320   2402   160   Filing a brief in support of an appeal   1403   280   2403   140   Request for oral hearing   1403   2803   2403   140   Request for exhaption   1503   1400   1503   1400   1503   1400   1503   1400   1503   1400   1503   1400   1503   1400   1503   1400   1503   1400   1503   1400   1503   1	Code (5) Code (5) Fee Paid	i i							$\vdash$	
1003   510   2003   255   Plant filing fee   160.00   1402   320   2402   160   Filing a brief in support of an appeal   1403   280   2403   140   Request for oral hearing   1451   1,510   Petition to institute a public use proceeding   1452   110   2452   55   Petition to institute a public use proceeding   1452   110   2452   150   2453   640   Petition to revive - unintentional   1451   1,510   Petition to revive - unintentional   1453   1,280   2453   640   Petition to revive - unintentional   1450   1,280   2501   640   Utility issue fee   1502   2453   640   Petition to revive - unintentional   1501   1,280   2502   230   Design issue fee   1502   2460   2502   230   Design issue fee   1460   130   Plant issue fee   1460   130								tady in Gran	$\vdash$	
1005   160   2005   80   Provisional filing fee   160.00   1451   1,510   1451   1,510   Petition to institute a public use proceeding   1452   110   1453   1,280   2453   640   Petition to revive – unavoidable   1453   1,280   2453   640   Petition to revive – unintentional   1450   1453   1450   1453   1450   1453   1450   1453   1450   1453   1450   1453   1450   1453   1450   1453   1450   1453   1450   1453   1450   1453   1450   1453   1450   1453   1450   1453   1450   1453   1450   1453   1450   1453   1450   1453   14		1402		2402		•	•	f an appeal		
SUBTOTAL (1) (3) 160.00 1452 110 2452 55 Petition to revive – unavoidable 1453 1,280 2453 640 Petition to revive – unavoidable 1453 1,280 2453 640 Petition to revive – unavoidable 1453 1,280 2453 640 Petition to revive – unavoidable 2453 640 Petition to revive – unavoidable 1453 1,280 2453 640 Petition to revive – unavoidable 2453 640 Petition to revive – unavoidable 1453 1,280 2453 640 Petition to revive – unavoidable 2501 640 Utility issue fee (Petition to revive – unavoidable 2501 640 Utility issue fee (Petition to revive – unavoid and to revive – unavoid fee (Petition for vive – unavoid and to revive – unavoid fee (Petition for vive – unavoid fee (Petition fee (Petition fee (Pe	1004 740 2004 370 Reissue filing fee	1403	280	2403	140	Request for	oral hearing			
2. EXTRA CLAIM FEES FOR UTILITY AND REISSUE Extra Fee from Fee Paid Independent Claims Multipla Dependent Large Entity Fee Fee Fee Code (\$) Fee Code (\$) Fee Description Code (\$) Code (\$) Fee Description Code (\$) Code (\$) Fee Code (\$) Fee Description Code (\$) Code (\$) Rependent Calms in excess of 20 1201 84 2201 42 Independent claims in excess of 3 1203 280 2203 140 Multiple dependent claims over original patent Code (\$) Code (\$) Ressue claims in excess of 20 and over original patent Code (\$) Code (\$) Ressue claims in excess of 20 and over original patent Code (\$) Code (\$) Ressue claims in excess of 20 and over original patent Code (\$) Code (\$) Ressue claims in excess of 20 and over original patent Code (\$) Code (\$) Ressue claims in excess of 20 and over original patent Code (\$) Code (\$) Ressue claims in excess of 20 Code (\$) Respective in excess of 20 Code (	1005 160 2005 80 Provisional filing fee 160.00	1451	1,510	1451	1,510	Petition to in	stitute a pub	lic use proceeding		
2. EXTRA CLAIM FEES FOR UTILITY AND REISSUE  Extra Fee from Claims below Fee Paid below Fee Paid 1502 460 2502 230 Design issue fee (or reissue)  Total Claims below Fee Paid 1503 620 2503 310 Plant issue fee (or reissue)  Independent Claims Small Emity 1805 180 1806 180 Submission of Information Disclosure Stmt 1807 50 1807 50 Processing fee under 37 CFR 1.17(q)  Itarge Entity Small Emity 1806 180 1808 180 Submission of Information Disclosure Stmt 1807 1809 1809 1809 1809 1809 1809 1809 1809	SUBTOTAL (1) (5) 160,00									
Extra   Fee from   Fee Paid   1502   460   2502   230   Design issue fee		1	-							
Total Claims		I		-				IB)		
Independent Caims  Multiple Dependent	Claims below Fee Paid					-				
Caims Multipla Dependent    1807   50   1807   50   Processing fee under 37 CFR 1.17(q)	Independent									
Large Entity Small Entity Fee Fee Fee Fee Fee Code (5) Code (5) 1202 18 2202 9 Claims in excess of 20 1201 84 2201 42 Independent claims in excess of 3 1203 280 2203 140 Multiple dependent claims in ot paid 1204 84 2204 42 "Reissue Independent claims over original patent over original patent over original patent SUBTOTAL (2) (\$) 0.00  "*Or number previously paid, if greater, For Reissues, see above   SUBMITTED BY   Sandra S. Lee   Registration No. (Attorney/Agent)   51,932   Recording each patent assignment per property (times number of properties)   Recording each patent assignment per property (times number of properties)   (37 CFR 1.129(a))   (37 CFR 1.129(a))   (37 CFR 1.129(b))   (37 CFR 1.12							_			
Fee Fee Fee Fee Fee Fee Fee Fee Fee Code (\$) Fee Description  1202 18 2202 9 Claims in excess of 20 1201 84 2201 42 Independent claims in excess of 3 1203 280 2203 140 Multiple dependent claims over original patent  1204 84 2204 42 "Reissue Independent claims over original patent  1205 18 2205 9 "Reissue claims in excess of 20 and over original patent  SUBTOTAL (2) (\$) 0.00  "or number previously paid, if greater, For Reissues, see above  SUBMITTED BY  Registration No. [Attorney/Agent]  Registration No. [Attorney/Agent]  Solution fee (spectiv)  Recording each patent assignment per property (times number of properties)  Filing a submission after final rejection (37 CFR 1,129(b))  For each additional invention to be examined (37 CFR 1,129(b))  Request for continued Examination (RCE)  Request for expedited examination of a design application  Other fee (specify)  Reduced by Basic Filing Fee Paid SUBTOTAL (3) (\$) 0.00  Telephone (212) 527-7735	Multiple Dependent =					•		- '''	$\vdash \vdash \vdash$	
Code (5) Code (5) P88 DESCRIPTION  1202 18 2202 9 Claims in excess of 20 1201 84 2201 42 Independent claims in excess of 3 1203 280 2203 140 Multiple dependent claims over original patent  1204 84 2204 42 "Reissue Independent claims over original patent  1205 18 2205 9 "Reissue claims in excess of 20 and over original patent  SUBTOTAL (2) (3) 0.00  "or number previously paid, if greater, For Reissues, see above  SUBMITTED BY  Complete (imes number of property (times number of prope	See Fee Fee Fee									
1201 84 2201 42 Independent claims in excess of 3 1203 280 2203 140 Multiple dependent claims in ot paid 1204 84 2204 42 "Reissue Independent claims over original patent 1205 18 2205 9 "Reissue claims in excess of 20 and over original patent  SUBTOTAL (2) (5) 0.00  "or number previously paid, if greater, For Reissues, see above  SUBMITTED BY  Name (Print/Type) Sandra S. Lee  1201 42 Independent claims in excess of 3 1810 740 2801 370 Request for each additional invention to be examined (37CFR 1.129(a)) 2810 370 Request for continued Examination (RCE) 2801 370 Request for expedited examination of a design application  Other fee (specify)  "Reduced by Basic Filing Fee Paid SUBTOTAL (3) (8) 0.00  Complete (if applicable)  Registration No. (Attorney/Agent)  Telephone (212) 527-7735		8021	40	8021	40	property (tim	nes number (	of properties)		
1201 84 2201 42 independent claims in excess of 3 1203 280 2203 140 Multiple dependent claims over original patent 1204 84 2204 42 "Reissue Independent claims over original patent 1205 18 2205 9 "Reissue claims in excess of 20 and over original patent  SUBTOTAL (2) (3) 0.00 Other fee (specify)  SUBMITTED BY  Complete (# applicable)  Registration No. (Attorney/Agent)  [1810 740 2810 370 For each additional invention to be examined (37CFR 1.129(b)) [1801 740 2801 370 Request for Continued Examination (RCE) or a design application  [1802 900 1802 900 Request for expedited examination of a design application  [1803 900 1802 900 Request for expedited examination of a design application  [1804 900 1802 900 Request for expedited examination of a design application  [1805 180 2 900 1802 900 Request for expedited examination of a design application  [1806 900 1802 900 Request for expedited examination of a design application  [1807 900 1802 900 Request for expedited examination of a design application  [1808 900 1802 900 Request for expedited examination of a design application  [1809 900 1802 900 Request for expedited examination of a design application  [1800 900 1802 900 Request for expedited examination of a design application  [1800 900 1802 900 Request for expedited examination of a design application  [1800 900 1802 900 Request for expedited examination of a design application  [1800 900 1802 900 Request for expedited examination of a design application  [1800 900 1802 900 Request for expedited examination of a design application  [1800 900 1802 900 1802 900 Request for expedited examination of a design application  [1800 900 1802 900 1802 900 Request for expedited examination of a design application  [1800 900 1802 900 1802 900 Request for expedited examination of a design application  [1800 900 1802 900 1802 900 1802 900 Request for examination of a design application  [1800 900 1802 900 1802 900 1802 900 1802 900 1802 900 1802 900 1802 900 1802 900 1802 900 1802 900 1802 900 1802 900 1802 900 1802 900 1802 900		1809	740	2809	370			final rejection		
1204 84 2204 42 "Reissue Independent claims over original patent source original patent sou		1810	740	2810	370	For each ad	ditional inve			
over original patent  1205 18 2205 9 "Reissue claims in excess of 20 and over original patent  SUBTOTAL (2) (\$\frac{1}{3}\) 0.00  "or number previously paid, if greater, For Reissues, see above  SUBMITTED BY  Regulation No. (Attorney/Agent)  Regulation 1802 900 Request for expedited examination of a design application  Other fee (specify)  "Reduced by Basic Filing Fee Paid SUBTOTAL (3) (\$\frac{1}{3}\) 0.00  Complete (if applicable)  Registration No. (Attorney/Agent)  Telephone (212) 527-7735					370					
1205 18 2205 9 "Rebsue claims in excess of 20 and over original patent Other fee (specify)  SUBTOTAL (2) (\$) 0.00  "Or number previously paid, if greater, For Reissues, see above  SUBMITTED BY  Complete (if applicable)  Registration No. (Attorney/Agent) 51,932  Telephone (212) 527-7735	over original patent					Request for	expedited ex	•	$\vdash \vdash \vdash$	
SUBTOTAL (2) (5) 0.00  "or number previously paid, if greater, For Reissues, see above  SUBMITTED BY  Complete (if applicable)  Registration No. (Attorney/Agent) 51,932  Telephone (212) 527-7735				l		of a design	application			
**or number previously paid, if greater, For Reissues, see above  SUBMITTED BY  Complete (if applicable)  Name (Print/Type) Sandra S. Lee  Registration No. (Attorney/Agent) 51,932  Telephone (212) 527-7735					ling Sec	Poid	SUBTO	FA1 (3) (5)		
SUBMITTED BY  Complete (if applicable)  Name (Print/Type)   Sandra S. Lee   Registration No. (Attorney/Agent)   51,932   Telephone   (212) 527-7735	1			odSIC F	miñ L66	7810	30510	(a) (a)	0.00	
Name (Print/Type) Sandra S. Lee Registration No. (Attorney/Agent) 51,932 Telephone (212) 527-7735				===			Complete (	if applicable)		
[(Attacley/Agest)					,932				<del></del>	
		Liveriorni	-угмдеги,	1=,	- '-					

# Certificate of Express Mailing Under 37 CFR 1.10

I hereby certify that this correspondence is being deposited with the United States Postal Service as Express Mail, Airbill No. in an envelope addressed to:

a 982102034-US

MS Provisional Patent Application Commissioner for Patents P.O. Box 1450 Alexandria, VA 22313-1450

October 8, 2003 Date

Typed or printed name of person signing Certificate

Note: Each paper must have its own certificate of mailing, or this certificate must identify each submitted paper.

Specification (12 pages); Claims (7 pages, claims 1-49);

Drawings (1 sheet);

Provisional Patent Application Transmittal (1 page);

Application Data Sheet (3 pages); Fee Transmittal for FY 2003 (1 page); and

Check in the amount of \$160.00 (Ch. No. 2364

#### **EXPRESS MAIL CERTIFICATE**

Date	Label No.
l her	by certify that, on the date indicated above, this paper or fee
was	eposited with the U.S. Postal Service & that it was
	ssed for delivery to the Mail Stop Provisional Patent
	ation, Commissioner for Patents, PO BOX 1450, Alexandria,
VA	2313-1450 by "Express Mail Post Office to Addressee"
sarvi	Α

PLEASE CHARGE ANY DEFICIENCY UP TO \$300.00 OR CREDIT ANY EXCESS IN THE FEES DUE WITH THIS DOCUMENT TO OUR DEPOSIT ACCOUNT NO. 04 - 0100

O . . . . . 050

Name (Print)

Signature

Customer No.: **07278** 

File No.: 1313/0200131-US0

# LATENT CARBON DIOXIDE GENERATING MATERIAL

#### FIELD OF THE INVENTION

This invention relates to nonwoven materials containing a chemical composition capable of generating carbon dioxide when activated.

10

15

20

25

5

# **BACKGROUND OF THE INVENTION**

It is known in the state of the art that the freshness of fruits and vegetables and other perishable food and agricultural materials can be preserved by the use of an environment rich in carbon dioxide. US Patent No. 5,489,399, hereby incorporated herein by reference in its entirety, discloses various materials useful in carbon dioxide gas generating compositions. This disclosure teaches that the carbon dioxide gas generating composition is usually packed into a bag made of nonwoven fabric, woven fabric, film formed with fine pores not passing a liquid therethrough or composite sheet of such materials and then placed in a package with fruit or vegetables. The disclosure teaches that either the alkali carbonate or the acid of the composition must be of low solubility, since if both are highly soluble the composition itself became liquid.

### SUMMARY OF THE INVENTION

It would be advantageous to have a delivery system for carbon dioxide gas generating compositions without the disadvantages of the prior art systems.

This invention provides a nonwoven carrier for carbon dioxide gas generating compositions which is a latent carbon dioxide gas generating material capable of activation under conditions of use so that a local environment rich in carbon dioxide may be established. As opposed to the prior art where all or most of the gas generating composition for a given container of produce is placed in a single location within the container, this invention provides a distribution of the particles or powder of the carbon dioxide gas generating composition throughout a substantial portion of the nonwoven carrier, which may then be installed in the container in any manner desired. Regardless of how the material is placed in a container, horizontal, vertical or otherwise, most of the powder is retained within the nonwoven carrier. The gas generating composition is activated by the absorption of water, which facilitates the chemical reaction of the acid and the base to produce carbon dioxide.

The prior art issue of the gas generating composition itself becoming liquid, either before, during or after reaction to form carbon dioxide, is obviated by distribution of the composition throughout a substantial portion of the nonwoven structure, which is produced from absorbent material which will absorb and retain any liquefied aspect of the composition within the material.

This invention provides a latent carbon dioxide gas generating material comprising:

- (A) layer 1 containing fiber and a binder, having a basis weight of from about 25 gsm to about 100 gsm and having inner and outer surfaces,
  - (B) layer 2 containing a carbon dioxide gas generating composition, having a basis weight of from about 5 gsm to about 300 gsm and having upper and lower surfaces, and
- 25 (C) layer 3 containing fiber and a binder, having a basis weight of from about 25 gsm to about 100 gsm and having inner and outer surfaces, where the inner surface of layer 1 is in contact with the upper surface of layer 2 and the inner surface of layer 3 is in contact with the lower surface of layer 2.

30

5

10

15

20

#### BRIEF DESCRIPTION OF THE FIGURE

Figure 1 shows plots of the generation of carbon dioxide measured by IR as a function of time for material having basis weights for the carbon dioxide gas generating composition of 5.6 gsm from Example 1, 11.3 gsm from Example 2, 22.5 gsm from Example 3 and 33.8 gsm from Example 4.

5

10

15

20

25

30

# DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

The latent carbon dioxide gas generating material of this invention comprises three layers, layers 1 and 3 containing fiber and binder which are above and below layer 2 which contains the carbon dioxide gas generating composition along with fiber and binder if desired. During early stages of manufacture, the gas generating composition, which may be powder, particulate or granular in form, has considerable freedom to move or migrate within layer 2 and to some extent into layer 1 and or layer 3, becoming intermingled with and dispersed within the fibrous structure. This movement may be slowed, directed or stopped altogether by the appropriate use and activation of binders in the material. While it is desirable for the gas generating composition to be distributed within the fibrous structure, it should not contribute to a dusting problem in the finished product, and it should be relatively if not totally immobile in the finished product. Thus, the finished material can be used in a wide variety of ways.

Layer 1 and layer 3 may be identical, similar or quite different in composition and properties. These layers have inner and outer surfaces, with the inner surface of each layer being in contact with one of the surfaces of layer 3. In the case where layer 2 is simply the gas generating composition with little or no fiber and binder, the particles of the gas generating composition may migrate into the fibrous structure of layer 1 and or layer 3, leaving areas of layer 1 and layer 3 intermittently in direct contact. This not the case where layer 2 contains fiber and binder, which effectively separates layer 1 from layer 3.

The fiber of layer 1, layer 3 and when present in layer 2 may be cellulosic fiber, synthetic fiber or a mixture thereof. A preferred embodiment uses cellulosic fiber. The fiber composition of the layers may be identical or different.

In a preferred embodiment of the material of this invention, the fiber and binder of a layer is from about 60 weight percent to about 95 weight percent fiber and from about 5 weight percent to about 40 weight percent binder, where the weight percentages are based on the total weight of fiber and binder in the layer.

The binder of layer 1, layer 3 and when present in layer 2 may be a synthetic binder fiber, a latex or a combination thereof. The binder composition of the layers may be identical or different. In one embodiment it is desirable that one or more layers contain a synthetic binder fiber in combination with a latex binder. In that case, the binder of the layer is a combination of from about 25 weight percent to about 75 weight percent synthetic binder fiber and from about 75 weight percent to about 25 weight percent latex where the weight percentages are based on the total weight of binder in the layer and the weight percent latex includes latex solids and fluid carrier. When a binder fiber, such as, for example, bicomponent fiber is used, it is generally mixed with fiber of the layer. When a latex binder is used, it may be applied to either or both of the surfaces of a layer.

The carbon dioxide gas generating composition of layer 2 contains a weak base and a weak acid or a salt which is convertible into an acid. Generally, the weak acid has a solubility of 0.5 g/100 g of water or greater at 30°C, and has a melting point of 30°C or greater. Examples of acids are citric acid, tartaric acid, succinic acid, fumaric acid, maleic acid, adipic acid, malic acid, oxalic acid, malonic acid, glutaric acid, phthalic acid, metaphosphoric acid, or wherein the salt which is convertible into an acid is an alkali metal salt of citric acid, tartaric acid, succinic acid, fumaric acid, maleic acid, adipic acid, malic acid, oxalic acid, malonic acid, glutaric acid, phthalic acid, metaphosphoric acid or a mixture thereof. Examples of salts which are convertible into acids are aluminum sulfate, calcium phosphate, alum, a double salt of an alum, potassium aluminum sulfate, sodium dihydrogen phosphate, potassium citrate, sodium maleate, potassium tartrate, sodium fumarate.

Generally, the weak base contains anionic carbonate or hydrogen carbonate, and, generally, the base contains as a cation an alkali metal, an alkaline earth metal or a transition metal. Examples of bases suitable for use in the practice of this invention are lead carbonate, calcium carbonate, barium carbonate, strontium carbonate, magnesium

carbonate, beryllium carbonate, lithium carbonate, sodium carbonate, potassium carbonate, rubidium carbonate, cesium carbonate, lead hydrogen carbonate, calcium hydrogen carbonate, barium hydrogen carbonate, strontium hydrogen carbonate, magnesium hydrogen carbonate, beryllium hydrogen carbonate, lithium hydrogen carbonate, sodium hydrogen carbonate, potassium hydrogen carbonate, rubidium hydrogen carbonate, cesium hydrogen carbonate, or a mixture thereof.

In a preferred composition the acid is citric acid and base is sodium hydrogen carbonate.

It is desirable that the ratio by weight of acid to base in the carbon dioxide gas generating composition is from about 10:1 to about 1:10, preferably, that the ratio by weight of acid to base in the carbon dioxide gas generating composition is from about 5:1 to about 1:5. It is desirable that the ratio of equivalents of acid to equivalents of base in the carbon dioxide gas generating composition is from about 5:1 to about 1:5, preferably, that the ratio of equivalent of acid to equivalents of base in the carbon dioxide gas generating composition is from about 3:2 to about 2:3

In another aspect of this invention, the latent carbon dioxide gas generating material further comprises a carrier having a basis weight of from about 10 gsm to about 40 gsm which is in contact with the outer surface of layer 1 or layer 3. The carrier may be a cellulosic tissue carrier or made of synthetic material, such as, for example, a polyolefin or polyester.

Desirably, the latent carbon dioxide gas generating material of this invention has a basis weight of from about 65 gsm to about 500 gsm. One desirable embodiment has a basis weight of from about 65 gsm to about 140 gsm, while an alternative desirable embodiment has a basis weight of from about 141 gsm to about 300 gsm, and another desirable embodiment has a basis weight of from about 301 gsm to about 500 gsm.

The carbon dioxide gas generating composition may be from about 3 weight percent to about 60 weight percent of the latent carbon dioxide gas generating material. In one embodiment, the carbon dioxide gas generating composition is from about 3 weight percent to about 20 weight percent based on the total weight of the material, while in another embodiment, the carbon dioxide gas generating composition is from about 21 weight percent to about 40 weight percent based on the total weight of the material, and

30

5

10

15

20

25

5

10

15

20

25

30

in a further embodiment, the carbon dioxide gas generating composition is from about 41 weight percent to about 60 weight percent based on the total weight of the material.

6

In one embodiment of this invention, the carbon dioxide gas generating composition contains a hydrophilic material with a hygroscopicity of from about 80 weight percent to about 250 weight percent based on the weight of the hydrophilic material at 30°C. The hydrophilic material may be a saccharide or derivative thereof, polyhydric alcohol or derivative thereof, polyacrylamide or derivative thereof, polyelectrolyte or a water absorbing polymer. Examples of hydrophilic materials are erythrose, threose, arabinose, xylose, lyxose, glucose, fructose, mannose, galactose, sorbitol, gluconic acid, sucrose, lactose, maltose, dextrin, amylose and hydroxymethyl cellulose.

The carbon dioxide gas generating composition may contain a hydrophobic material, such as, for example, a wax, a fatty acid or a salt or ester of a fatty acid.

There are a number of manufacturing processes that can be used to produce the latent carbon dioxide gas generating material of this invention. For example, one manufacturing process is an airlaid process which is used to produce an airlaid web which is typically prepared by disintegrating or defiberizing a pulp sheet or sheets typically by a hammermill to provide substantially opened fibers. The opened fibers are then air conveyed to forming heads on the airlaid web forming machine. Several manufacturers make defiberized pulp sheet airlaid web forming machines including M&J Fibretech of Denmark and Dan-Web, also of Denmark. The forming heads can include rotating or agitated drums, generally in a race track configuration which serve to maintain fiber separation until the fibers are pulled by vacuum onto a foraminous condensing drum or foraminous forming conveyor. Other fibers, such as a synthetic thermoplastic fiber, or superabsorbent fiber can also be introduced to the forming head through a fiber dosing system which includes a fiber opening, a dosing unit and an air conveyor. Non-fibrous materials, such as, for example a carbon dioxide gas generating composition and various additives, such as, for example, a hydrophilic material such as a superabsorbent polymer (SAP) or a hydrophobic material in powder form, particulate or granules can also be added to the forming head by a dosing system.

Typically, the airlaid web is transferred from the condensing drum or forming conveyor to a calender or other densification stage to densify the web, increase its strength and control web thickness. The fibers of the web are then bonded by application of a latex spray or foam addition system, followed by drying or curing. Alternatively, or additionally, any thermoplastic fiber present in the web can be softened or partially melted by application of heat to bond the fibers of the web. The bonded web can then be calendered a second time to increase strength or emboss the web with a design or pattern. If thermoplastic fibers are present, hot calendering can be employed to impart patterned bonding to the web. Water can be added to the web if necessary to maintain specified or desired moisture content, to minimize dusting and to reduce the buildup of static electricity.

The airlaid manufacturing system has the advantage that it is a continuous process which employs a series of unit operations to produce a unitary material. Alternatively, various elements of the material can be produced as individual components and then assembled in a converting operation.

The bulk fibers of the present invention may be natural, synthetic, or a mixture thereof. In one embodiment, the fibers may be cellulose-based pulp fibers, one or more synthetic fibers, or a mixture thereof. Any cellulose fibers known in the art, including cellulose fibers of any natural origin, such as those derived from wood pulp, may be used in a cellulosic layer. Preferred cellulose fibers include, but are not limited to, digested fibers, such as kraft, prehydrolyzed kraft, soda, sulfite, chemi-thermal mechanical, and thermo-mechanical treated fibers, derived from softwood, hardwood or cotton linters. More preferred cellulose fibers include, but are not limited to, kraft digested fibers, including prehydrolyzed kraft digested fibers. Suitable for use in this invention are the cellulose fibers derived from softwoods, such as pines, firs, and spruces. Other suitable cellulose fibers include those derived from Esparto grass, bagasse, kemp, flax and other lignaceous and cellulosic fiber sources. Suitable cellulose fibers include, but are not limited to, bleached Kraft southern pine fibers sold under the trademark FOLEY FLUFFS®, Buckeye Technologies Inc., Memphis, Tennessee. Synthetic fibers include for example polyester such as PET, nylon, polyethylene or polypropylene.

8

5

10

15

20

25

30

Also preferred is cotton linter pulp, chemically modified cellulose such as crosslinked cellulose fibers and highly purified cellulose fibers, such as Buckeye HPF each available from Buckeye Technologies Inc., Memphis, Tennessee.

The fiber-containing layer may also include thermoplastic binding material, which may be blended with the cellulosic or synthetic fibers. Suitable thermoplastic binding material includes thermoplastic fibers, such as bicomponent thermoplastic fibers (bico). Preferred thermoplastic binding fibers provide enhanced adhesion for a wide range of materials, including synthetic and natural fibers, particles, and synthetic and natural carrier sheets. An exemplary thermoplastic bico fiber is Celbond Type 255 Bico fiber from KoSa, Charlotte, North Carolina.

Bicomponent fibers having a core and sheath are known in the art. Many varieties are used in the manufacture of nonwoven materials, particularly those produced by airlaid techniques. Various bicomponent fibers suitable for use in the present invention are disclosed in U.S. Patents 5,372,885 and 5,456,982, both of which are hereby incorporated by reference in their entirety. Examples of bicomponent fiber manufacturers include KoSa (Salisbury, NC), Trevira (Bobingen, Germany) and ES Fiber Visions (Athens, GA).

Bicomponent fibers may incorporate a variety of polymers as their core and sheath components. Bicomponent fibers that have a PE (polyethylene) or modified PE sheath typically have a PET (polyethyleneterephthalate) or PP (polypropylene) core. In one embodiment, the bicomponent fiber has a core made of polyester and sheath made of polyethylene. The denier of the fiber preferably ranges from about 1.0 dpf to about 4.0 dpf, and more preferably from about 1.5 dpf to about 2.5 dpf. The length of the fiber is preferably from about 3 mm to about 12 mm, more preferably from about 4.5 mm to about 7.5 mm.

Various geometries can be used for the bicomponent fiber of this invention, including concentric, eccentric, islands-in-the-sea, and side-by-side. The relative weight percentages of the core and sheath components of the total fiber may be varied.

The present invention may also include a latex binder. Preferred binders include but are not limited to ethyl vinyl acetate copolymer such as AirFlex 124 (Air Products, Allentown, Pennsylvania) with 10% solids and 0.75% by weight Aerosol OT (Cytec

Industries, West Paterson, New Jersey), which is an anionic surfactant. Other classes of emulsion polymer binders such as styrene-butadiene and acrylic binders may also be used.

Various materials, structures and manufacturing processes useful in the practice of this invention are disclosed in U.S. Patent No.s 6,241,713; 6,353,148; 6,353,148; 6,171,441; 6,159,335; 5,695,486; 6,344,109; 5,068,079; 5,269,049; 5,693,162; 5,922,163; 6,007,653; and 6,355,079; and in U.S. Patent applications with serial numbers and filing dates, 09/211,935 filed 12/15/98; 09/232,783 filed 1/19/99; 09/719,338 filed 1/17/01; 09/475,850 filed 12/30/99; 09/469,930 filed 12/21/99; 09/578,603 filed 5/25/00; 05/593,409 filed 6/14/00; 09/325,764 filed 6/8/99 allowed; 09/774,248 filed 1/30/01; and 09/854,179 filed 5/11/01, all of which are hereby incorporated by reference in their entirety.

#### **EXAMPLES**

#### 15 Example 1:

5

10

30

Handsheets were formed on a lab airlaid forming device in two layers. The pads were built on top of a Spunbond-Meltblown-Meltblown-Spunbond (SMMS) polypropylene hydrophobic carrier having a basis weight of 17 gsm, NW 58 from First Quality Nonwovens, Great Neck, NY.

Layer 1 was a blend of 55 gsm cellulose fluff, FOLEY FLUFFS<sup>®</sup>, Buckeye,
Perry, FL, and 9.7 gsm 2.0 dpf x 6mm bicomponent fiber with a polyester core and a
polyethylene sheath, F55 from KoSa, Charlotte, NC, which was deposited directly on the
carrier. Then 5.6 gsm of a pre-mixed powder of sodium bicarbonate and acetylsalicylic
acid from CO<sub>2</sub> Technologies, West Des Moines, IA, was added by hand. The powder
had an 88:12 base:acid powder content ratio by weight. The carrier side was sprayed
with 11 gsm of an ethylene vinyl acetate latex with 20 percent solids, EP-1188 from Air
Products, Allentown PA.

Layer 2 was a blend of 110 gsm cellulose fluff, FOLEY FLUFFS<sup>®</sup>, and 19.4 gsm bicomponent fiber, KoSa F55, 2.0 dpf x 6mm, which was deposited on top of the powder. The materials were pressed with shims at 5.08 mm (200 mils) thickness and 239.2 kPa

(5000 psi) pressure with platens heated to 150°C for 1 minute. The pads were then cured for 15 minutes at 145°C.

#### Example 2:

Handsheets were formed as described in Example 1, except that 11.3 gsm of a pre-mixed powder of sodium bicarbonate and acetylsalicylic acid with an 88:12 base:acid powder content ratio by weight from CO<sub>2</sub> Technologies, was added by hand.

#### Example 3:

Handsheets were formed as described in Example 1, except that 22.5 gsm of a pre-mixed powder of sodium bicarbonate and acetylsalicylic acid with an 88:12 base:acid powder content ratio by weight from CO<sub>2</sub> Technologies, was added by hand.

#### Example 4:

Handsheets were formed as described in Example 1, except that 33.8 gsm of a pre-mixed powder of sodium bicarbonate and acetylsalicylic acid with an 88:12 base:acid powder content ratio by weight from CO<sub>2</sub> Technologies, was added by hand.

Examples 1-4 were submitted for a gas generation study. A graph of the outcome of that study appears as Figure 1.

#### Example 5:

20

25

30

Nonwoven material was made on a Dan-Web type pilot airlaid machine using three forming heads to deposit three layers on a Spunbond-Meltblown-Meltblown-Spunbond (SMMS) polypropylene hydrophobic carrier having a basis weight of 17 gsm, NW 58 from First Quality Nonwovens, Great Neck, NY.

Layer 1 was a blend of 29.2 gsm cellulose fluff, FOLEY FLUFFS® and 5.1 gsm of a 1.7 dtex x 4 mm bicomponent fiber with a polypropylene core and a polyethylene sheath, AL-Adhesion-C, Fiber Visions Covington, GA, was deposited on the carrier. This layer was sprayed with 5 gsm of Airflex 192, an ethylene vinyl acetate latex used at 15 percent solids, from Air Products, Allentown, PA.

Layer 2 was a blend of 29.2 gsm of FOLEY FLUFFS<sup>®</sup>, 5.1 gsm Fiber Visions bicomponent fiber, AL-Adhesion-C, 1.7 dtex x 4 mm, and 22.5 gsm of a blend of sodium bicarbonate from Church&Dwight, Princeton, NJ, and citric acid powders. The blend ratio of the powder was 88:12 sodium bicarbonate: citric acid by weight.

Layer 3 was a blend of 29.2 gsm FOLEY FLUFFS® and 5.1 gsm Fiber Visions bicomponent fiber, AL-Adhesion-C, 1.7 dtex x 4 mm. This layer was sprayed with 2.5 gsm of Airflex 192, 15% solids. The material was then pressed to a target caliper of 2.74 mm.

#### 10 Example 6:

5

15

Nonwoven material was made as in Example 5, except that in Layer 1 the fiber blend contained 36.3 gsm of FOLEY FLUFFS® and 6.3 gsm of Fiber Visions bicomponent fiber, AL-Adhesion-C, Layer 2 used 36.3 gsm of FOLEY FLUFFS® and 6.3 gsm of Fiber Visions AL-Adhesion-C, and 22.5 gsm of the bicarbonate citric acid blend and Layer 3 used 36.3 gsm of FOLEY FLUFFS® and 6.3 gsm of Fiber Visions bicomponent fiber, AL-Adhesion-C. Samples were pressed to a target caliper of 3.16 mm.

# Example 7:

Nonwoven material was made as in Example 5, except that in Layer 1, the fiber blend contained 43.4 gsm of FOLEY FLUFFS® and 7.6 gsm of Fiber Visions bicomponent fiber, AL-Adhesion-C, Layer 2 used 43.6 gsm of FOLEY FLUFFS® and 7.6 gsm of Fiber Visions AL-Adhesion-C, and 22.5 gsm of the bicarbonate citric acid blend and Layer 3 used 43.4 gsm of FOLEY FLUFFS® and 7.6 gsm of Fiber Visions bicomponent fiber, AL-Adhesion-C. Samples were pressed to a target caliper of 3.61 mm.

#### Example 8:

5

10

15

25

Nonwoven material was made as in Example 5, except that in Layer 1, the fiber blend contained 23.4 gsm of FOLEY FLUFFS® and 5.1 gsm of a 2.2 dtex x 3 mm bicomponent fiber with a polyethyleneterephthalate core and a polyethylene sheath, Merge 1663 from Trevira, Frankfurt am Main, Germany, Layer 2 used 43.6 gsm of FOLEY FLUFFS® and 5.1 gsm Merge 1663, and 22.5 gsm of a bicarbonate citric acid blend with base to acid ratio 4:1 by weight and Layer 3 used 43.4 gsm of FOLEY FLUFFS® and 5.1 gsm Merge 1663. Samples were pressed to a target caliper of 2.74 mm. A sample of the material was activated with water and carbon dioxide gas was generated.

#### Example 9:

Nonwoven material was made as in Example 8, except that in Layer 1 the fiber blend contained 26.7 gsm of FOLEY FLUFFS® and 7.8 gsm of Merge 1663, Layer 2 used 26.7 gsm of FOLEY FLUFFS® and 7.8 gsm Merge 1663, and 102 gsm of the bicarbonate citric acid blend and Layer 3 used 26.7 gsm of FOLEY FLUFFS® and 7.8 gsm Merge 1663. Samples were pressed to a target caliper of 2.8 mm. A sample of the material was activated with water and carbon dioxide gas was generated.

## 20 **Example 10:**

Nonwoven material was made as in Example 8, except that in Layer 1, the fiber blend contained 40 gsm of FOLEY FLUFFS® and 9.4 gsm of Merge 1663, Layer 2 used 40 gsm of FOLEY FLUFFS® and 9.4 gsm Merge 1663, and 102 gsm of the bicarbonate citric acid blend and Layer 3 used 40 gsm of FOLEY FLUFFS® and 9.4 gsm Merge 1663. Samples were pressed to a target caliper of 3.3 mm. A sample of the material was activated with water and carbon dioxide gas was generated.

#### **CLAIMS**

What is claimed is:

- 1. A latent carbon dioxide gas generating material comprising:
- (A) layer 1 containing fiber and a binder, having a basis weight of from about 25 gsm to about 100 gsm and having inner and outer surfaces,
- (B) layer 2 containing a carbon dioxide gas generating composition, having a basis weight of from about 5 gsm to about 300 gsm and having upper and lower surfaces, and
- (C) layer 3 containing fiber and a binder, having a basis weight of from about 25 gsm to about 100 gsm and having inner and outer surfaces, where the inner surface of layer 1 is in contact with the upper surface of layer 2 and the inner surface of layer 3 is in contact with the lower surface of layer 2.
- 2. The material of claim 1, further comprising a carrier having a basis weight of from about 10 gsm to about 40 gsm which is in contact with the outer surface of layer 1.
- 3. The material of one of the previous claims, wherein the fiber of layer 1 is cellulosic fiber, synthetic fiber or a mixture thereof.
  - 4. The material of claim 3, wherein the fiber of layer 1 is cellulosic fiber.
- 5. The material of one of the previous claims, wherein the binder of layer 1 is a synthetic binder fiber, a latex or a combination thereof.
- 6. The material of claim 5, wherein the synthetic binder fiber of layer 1 is a bicomponent fiber.
- 7. The material of one of the previous claims, wherein layer 1 contains from about 60 weight percent to about 95 weight percent fiber and from about 5 weight percent

to about 40 weight percent binder, where the weight percentages are based on the total weight of fiber and binder in the layer.

- 8. The material of one of the previous claims, wherein layer 1 contains a synthetic binder fiber in combination with a latex binder.
- 9. The material of claim 8, wherein the binder of layer 1 is a combination of from about 25 weight percent to about 75 weight percent synthetic binder fiber and from about 75 weight percent to about 25 weight percent latex where the weight percentages are based on the total weight of binder and the weight percent latex includes latex solids and fluid carrier.
- 10. The material of one of the previous claims, wherein layer 2 contains a carbon dioxide gas generating composition comprising a weak base and a weak acid.
- 11. The material of claim 10, wherein the weak acid has a solubility of 0.5 g/100 g of water or greater at 30°C, and has a melting point of 30°C or greater.
- 12. The material of one of the previous claims, wherein layer 2 contains a salt which is convertible into an acid.
- 13. The material of claim 11, wherein the acid is citric acid, tartaric acid, succinic acid, fumaric acid, maleic acid, adipic acid, malic acid, oxalic acid, malonic acid, glutaric acid, phthalic acid, metaphosphoric acid, or wherein the salt which is convertible into an acid is an alkali metal salt of citric acid, tartaric acid, succinic acid, fumaric acid, maleic acid, adipic acid, malic acid, oxalic acid, malonic acid, glutaric acid, phthalic acid, metaphosphoric acid or a mixture thereof.
- 14. The material of claim 10, wherein the weak base contains anionic carbonate or hydrogen carbonate.

- 15. The material of claim 14, wherein the base contains as a cation an alkali metal, an alkaline earth metal or a transition metal.
- 16. The material of claim 15, wherein the base is, lead carbonate, calcium carbonate, barium carbonate, strontium carbonate, magnesium carbonate, beryllium carbonate, lithium carbonate, sodium carbonate, potassium carbonate, rubidium carbonate, cesium carbonate, lead hydrogen carbonate, calcium hydrogen carbonate, barium hydrogen carbonate, strontium hydrogen carbonate, magnesium hydrogen carbonate, beryllium hydrogen carbonate, lithium hydrogen carbonate, sodium hydrogen carbonate, potassium hydrogen carbonate, rubidium hydrogen carbonate, cesium hydrogen carbonate, or a mixture thereof.
- 17. The material of claim 13, wherein the salt which is convertible into an acid is aluminum sulfate, calcium phosphate, alum, a double salt of an alum, potassium aluminum sulfate, sodium dihydrogen phosphate, potassium citrate, sodium maleate, potassium tartrate, sodium fumarate, .
- 18. The material of claim 10, wherein the acid is citric acid and base is sodium hydrogen carbonate.
- 19. The material of one of the previous claims, wherein layer 2 contains a carbon dioxide gas generating composition mixed with fiber and binder.
- 20. The material of claim 19, wherein the fiber of layer 2 is cellulosic fiber, synthetic fiber or a mixture thereof.
  - 21. The material of claim 20, wherein the fiber of layer 2 is cellulosic fiber.
- 22. The material of one of claims 19-21, wherein the binder of layer 2 is a synthetic binder fiber, a latex or a combination thereof.

- 23. The material of claim 22, wherein the synthetic binder fiber of layer 2 is a bicomponent fiber.
- 24. The material of one of the previous claims, wherein layer 2 contains fiber and binder which are from about 60 weight percent to about 95 weight percent fiber and from about 5 weight percent to about 40 weight percent binder, where the weight percentages are based on the total weight of the fiber and binder in the layer.
- 24. The material of one of claims 19-23, wherein layer 2 contains a synthetic binder fiber in combination with a latex binder.
- 26. The material of claim 24, wherein the binder of layer 2 is a combination of from about 25 weight percent to about 75 weight percent synthetic binder fiber and from about 75 weight percent to about 25 weight percent latex where the weight percentages are based on the total weight of binder and the weight percent latex includes latex solids and fluid carrier.
- 27. The material of one of the previous claims, wherein the fiber of layer 3 is cellulosic fiber, synthetic fiber or a mixture thereof.
  - 28. The material of claim 27, wherein the fiber of layer 3 is cellulosic fiber.
- 29. The material of one of the previous claims, wherein the binder of layer 3 is a synthetic binder fiber, a latex or a combination thereof.
- 30. The material of claim 29, wherein the synthetic binder fiber of layer 3 is a bicomponent fiber.
- 31. The material of claim 27, wherein layer 3 contains from about 60 weight percent to about 95 weight percent fiber and from about 5 weight percent to about 40


weight percent binder, where the weight percentages are based on the total weight of the layer.

- 32. The material of one of the previous claims, wherein layer 3 contains a synthetic binder fiber in combination with a latex binder.
- 33. The material of claim 32, wherein the binder of layer 3 is a combination of from about 25 weight percent to about 75 weight percent synthetic binder fiber and from about 75 weight percent to about 25 weight percent latex where the weight percentages are based on the total weight of binder and the weight percent latex includes latex solids and fluid carrier.
- 34. The material of one of the previous claims, wherein the basis weight of the material is from about 65 gsm to about 500 gsm.
- 35. The material of claim 34, wherein the basis weight of the material is from about 65 gsm to about 140 gsm.
- 36. The material of claim 34, wherein the basis weight of the material is from about 141 gsm to about 300 gsm.
- 37. The material of claim 34, wherein the basis weight of the material is from about 301 gsm to about 500 gsm.
- 38. The material of one of the previous claims, wherein the carbon dioxide gas generating composition is from about 3 weight percent to about 20 weight percent based on the total weight of the material.
- 39. The material of one of claims 1-37, wherein the carbon dioxide gas generating composition is from about 21 weight percent to about 40 weight percent based on the total weight of the material.

- 40. The material of one of claims 1-37, wherein the carbon dioxide gas generating composition is from about 41 weight percent to about 60 weight percent based on the total weight of the material.
- 41. The material of one of the previous claims, wherein the ratio by weight of acid to base in the carbon dioxide gas generating composition is from about 10:1 to about 1:10.
- 42. The material of claim 41, wherein the ratio by weight of acid to base in the carbon dioxide gas generating composition is from about 5:1 to about 1:5.
- 43. The material of one of the previous claims, wherein the ratio of equivalents of acid to equivalents of base in the carbon dioxide gas generating composition is from about 5:1 to about 1:5.
- 44. The material of claim 43, wherein the ratio of equivalent of acid to equivalents of base in the carbon dioxide gas generating composition is from about 3:2 to about 2:3.
- 45. The material of one of the previous claims, wherein the carbon dioxide gas generating composition contains a hydrophilic material with a hygroscopicity of from about 80 weight percent to about 250 weight percent based on the weight of the hydrophilic material at 30°C.
- 46. The material of claim 45, wherein the hydrophilic material is a saccharide or derivative thereof, polyhydric alcohol or derivative thereof, polyacrylamide or derivative thereof, polyelectrolyte or a water absorbing polymer.

- 47. The material of claim 46, wherein the hydrophilic material is erythrose, threose, arabinose, xylose, lyxose, glucose, fructose, mannose, galactose, sorbitol, gluconic acid, sucrose, lactose, maltose, dextrin, amylose or hydroxymethyl cellulose.
- 48. The material of one of the previous claims, wherein the carbon dioxide gas generating composition contains a hydrophobic material.
- 49. The material of claim 48, wherein the hydrophobic material is a wax, a fatty acid or a salt or ester of a fatty acid.

Figure 1



#### Applicati n Data Sheet

#### **Application Information**

Application Type:: Provisional

Subject Matter:: Utility

Suggested Group Art Unit:: N/A

CD-ROM or CD-R?:: None

Sequence submission?:: None

Computer Readable Form (CRF)?:: No

Title:: LATENT CARBON DIOXIDE GENERATING

**MATERIAL** 

Attorney Docket Number:: 01313/0200131-US0

Request for Early Publication?:: No

Request for Non-Publication?:: No

Small Entity?:: No

Petition included?:: No

Secrecy Order in Parent Appl.?:: No

#### **Applicant Information**

Applicant Authority Type:: Inventor

Primary Citizenship Country:: Canada

Status:: Full Capacity

Given Name:: Brian

Middle Name:: E.

Family Name:: Boehmer

City of Residence:: Bartlett

State or Province of Residence:: TN

Country of Residence:: US

Street of mailing address:: 6348 Daybreak Drive

City of mailing address:: Bartlett

State or Province of mailing address:: TN

Postal or Zip Code of mailing address:: 38135

Applicant Authority Type:: Inventor

Primary Citizenship Country:: US

Status:: Full Capacity

Given Name:: Joshua

Middle Name:: D.

Family Name:: Crews

City of Residence:: Memphis

State or Province of Residence:: TN

Country of Residence:: US

Street of mailing address:: 1405 Summer Brook Lane, Apt. 5

City of mailing address:: Memphis

State or Province of mailing address:: TN

Postal or Zip Code of mailing address:: 38134

Applicant Authority Type:: Inventor

Primary Citizenship Country:: US

Status:: Full Capacity

Given Name:: John Middle Name:: P.

Family Name:: Erspamer
City of Residence:: Lakeland

State or Province of Residence:: TN

Country of Residence:: US

Street of mailing address:: 9580 Elm Point Cove

City of mailing address:: Lakeland

State or Province of mailing address:: TN

Postal or Zip Code of mailing address:: 38002

**Correspondence Information** 

Correspondence Customer Number:: 07278

# Repr s ntative Information

Representative Customer Number:: 07278

**Assignee Information** 

Assignee name:: BKI Holding Corporation

Street of mailing address:: 300 Delaware Avenue

Suite 900

City of mailing address:: Wilmington

State or Province of mailing address:: DE

Postal or Zip Code of mailing address:: 19081

# Document made available under the Patent Cooperation Treaty (PCT)

International application number: PCT/US04/033540

International filing date: 07 October 2004 (07.10.2004)

Document type: Certified copy of priority document

Document details: Country/Office: US

Number: 60/509,820

Filing date: 08 October 2003 (08.10.2003)

Date of receipt at the International Bureau: 18 November 2004 (18.11.2004)

Remark: Priority document submitted or transmitted to the International Bureau in

compliance with Rule 17.1(a) or (b)

